

# TLF- HT

## Trican Linear Fluid Loss – High Temp.

### Applications:

TLF-HT is a water soluble, high-temperature fluid loss control additive used in cementing applications. It is a mixture of synthetic fluid loss polymers and superplasticizers and can be utilized in virtually any cement application, except in the presence of chloride ions.

### Properties:

Appearance .....Light Brown Powder  
Specific Gravity ..... 1.3  
Solubility ..... Complete in water

### Advantages:

- Wide temperature application range (95°F to 480°F).
- Can be pre-hydrated or dry-blended.
- Linear fluid loss properties.
- Minimal retardation effects.

### Disadvantages:

- Reduced Fluid Loss Properties in the presence of sodium & calcium chlorides.

### Handling Precautions:

- Contact with skin and eyes should be avoided.
- Work in a ventilated area.
- Use of goggles & dust mask required.



March 19, 2003

Cementing – Fluid Loss

Page 1

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information.

Liberty Pressure Pumping, L.P., 1517 Centre Place Drive #320, Denton, TX 76205, 940-243-1120

