

# LBK-26EP

## Encapsulated Persulfate

11110-011

<b>General Information:</b>	LBK-26EP is an encapsulated persulfate breaker for fracturing fluids. It gives delayed breaks relative to uncoated ammonium persulfate and so can be used at higher temperatures.
<b>Physical Properties:</b>	LBK-26EP is a white solid in the form of uniform beads. It is very slowly soluble in water.
<b>Chemical Description:</b>	LBK-26EP contains ammonium persulfate surrounded by a proprietary encapsulating agent.
<b>Recommended Uses:</b>	LBK-26EP is typically used in fracturing treatments at loadings of 0.2 to 2.0 pounds of product per thousand gallons of fluid. Fluid temperatures most appropriate for LBK-26EP are from around 150°F to 250°F.
<b>Limitations:</b>	LBK-26EP may be ineffective at temperatures below 150°F unless very long break times are required.
<b>Packaging:</b>	LBK-26EP is available in 55-pound recloseable poly pails.
<b>DOT Information:</b>	<b>AMMONIUM PERSULFATE MIXTURE, 5.1, UN 1444, PG III.</b>



LIBERTY



June 21, 2008

Fracturing – Breakers

Page 1

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information.